ESP32-C3 Series SoC

Errata

Introduction

This document describes known errata in ESP32-C3 series of SoCs.



Contents

Ch	nip Ic	lentification	3
1	Chip I	Revision	3
2	Additi	onal Methods	5
Er	rata	Description	7
3	SAR	ADC .	7
	3.1	The Digital Controller of SAR ADC2 cannot work	7
	3.2	SAR ADC Cannot Sample Sufficient Data in DMA Continuous Conversion Mode after Restart	7
Re	late	d Documentation and Resources	S
Re	visio	on History	10

Chip Identification

Note:

Check the link or the QR code to make sure that you use the latest version of this document: https://espressif.com/sites/default/files/documentation/esp32-c3_errata_en.pdf



1 Chip Revision

Espressif is introducing vM.X numbering scheme to indicate chip revisions.

- **M** Major number, indicating the major revision of the chip product. If this number changes, it means the software used for the previous version of the product is incompatible with the new product, and the software version shall be upgraded for the use of the new product.
- **X** Minor number, indicating the minor revision of the chip product. If this number changes, it means the software used for the previous version of the product is compatible with the new product, and there is no need to upgrade the software.

The vM.X scheme replaces previously used chip revision schemes, including ECOx numbers, Vxxx, and other formats if any.

The chip revision is identified by:

• eFuse field EFUSE_RD_MAC_SPI_SYS_5_REG[25:23] and EFUSE_RD_MAC_SPI_SYS_3_REG[20:18]

Chip Revision eFuse Bit v0.0 v0.1 v0.2 v0.3 v0.4 v1.1 EFUSE_RD_MAC_SPI_SYS_5_REG[25] 0 0 0 0 0 0 **Major Number** EFUSE_RD_MAC_SPI_SYS_5_REG[24] 0 0 0 0 0 1 EFUSE_RD_MAC_SPI_SYS_5_REG[23] 0 0 0 0 0 0 EFUSE_RD_MAC_SPI_SYS_3_REG[20] 0 0 0 0 1 0 **Minor Number** EFUSE_RD_MAC_SPI_SYS_3_REG[19] 0 0 0 0 1 1 EFUSE_RD_MAC_SPI_SYS_3_REG[18] 1 0 0 0 1 1

Table 1: Chip Revision Identification by eFuse Bits

• Main Die line in chip marking




Figure 1: Chip Marking Diagram

Table 2: Chip Revision Identification by Silk Print

Chip Revision	Main Die
v0.0	XAXXXXXXX
v0.1	XBXXXXXXX
v0.2	XCXXXXXXX
v0.3	XDXXXXXXX
v0.4	XEXXXXXXX
v1.1	XHXXXXXXX

• Specification Identifier line in module marking




Figure 2: Module Marking Diagram

Table 3: Chip Revision Identification by Module Marking

Chip Revision	Specification Identifier ¹
v0.0	-
v0.1	_
v0.2	-
v0.3	XXXXX
v0.4	M4XXXX
v1.1	-

^{1 –} means modules with this chip revision are not mass produced.

Note:

- Information about ESP-IDF release that supports a specific chip revision is provided in <u>Compatibility Between</u> ESP-IDF Releases and Revisions of Espressif SoCs.
- For more information about the chip revision upgrade and their identification of ESP32-C3 series products, please refer to ESP32-C3 Product/Process Change Notifications (PCN).
- For more information about the chip revision numbering scheme, see Compatibility Advisory for Chip Revision Numbering Scheme.

2 Additional Methods

Some errors in the chip product don't need to be fixed at the silicon level, or in other words in a new chip revision.

In this case, the chip may be identified by **Date Code** in chip marking (see Figure 1). For more information, please refer to *Espressif Chip Packaging Information*.

Modules built around the chip may be identified by **PW Number** in product label (see Figure 3). For more information, please refer to *Espressif Module Packaging Information*.



Figure 3: Module Product Label

Note:

Please note that PW Number is only provided for reels packaged in aluminum moisture barrier bags (MBB).

Errata Description

Table 4: Errata Summary

	Affected Revisions						
Category	Description	v0.0	v0.1	v0.2	v0.3	v0.4	v1.1
SAR ADC	3.1 The Digital Controller of SAR ADC2 cannot work	Υ	Υ	Υ	Υ	Υ	Υ
SAN ADC	3.2 SAR ADC Cannot Sample Sufficient Data in DMA	V	V	V	V	V	V
	Continuous Conversion Mode after Restart	Y	Y	Y	Y	Y	Y

3 SAR ADC

3.1 The Digital Controller of SAR ADC2 cannot work

Description

The Digital Controller of SAR ADC2 may receive a false sampling enable signal. In such a case, the controller will enter an inoperative state.

Workarounds

It is suggested to use SAR ADC1.

Solution

No fix scheduled.

3.2 SAR ADC Cannot Sample Sufficient Data in DMA Continuous Conversion Mode after Restart

Description

In DMA continuous conversion mode, if the SAR ADC is stopped and then restarted, the internal hardware counter that counts ADC samples will not be automatically cleared, and there is no dedicated register to manually clear it.

Consequently, users might encounter scenarios such as:

- Garbled sampling results
- Samples fewer than the configured value

Workarounds

Before starting the ADC continuous conversion:

- 1. Reset the ADC by first setting and then clearing SYSTEM APB SARADC RST
- 2. Sequentially configure the 16-bit APB_SARADC_APB_ADC_EOF_NUM field with all values ranging from the previously configured value down to 0, so as to clear the ADC sample counter

Note that this flow may take around 14 ms at most.

Solution

No fix scheduled.

Related Documentation and Resources

Related Documentation

- ESP32-C3 Series Datasheet Specifications of the ESP32-C3 hardware.
- ESP32-C3 Technical Reference Manual Detailed information on how to use the ESP32-C3 memory and peripherals.
- ESP32-C3 Hardware Design Guidelines Guidelines on how to integrate the ESP32-C3 into your hardware product.
- Certificates

https://espressif.com/en/support/documents/certificates

• ESP32-C3 Product/Process Change Notifications (PCN)

https://espressif.com/en/support/documents/pcns?keys=ESP32-C3

• ESP32-C3 Advisories - Information on security, bugs, compatibility, component reliability.

https://espressif.com/en/support/documents/advisories?keys=ESP32-C3

 Documentation Updates and Update Notification Subscription https://espressif.com/en/support/download/documents

Developer Zone

- ESP-IDF Programming Guide for ESP32-C3 Extensive documentation for the ESP-IDF development framework.
- ESP-IDF and other development frameworks on GitHub.

https://github.com/espressif

• ESP32 BBS Forum – Engineer-to-Engineer (E2E) Community for Espressif products where you can post questions, share knowledge, explore ideas, and help solve problems with fellow engineers.

https://esp32.com/

• The ESP Journal - Best Practices, Articles, and Notes from Espressif folks.

https://blog.espressif.com/

• See the tabs SDKs and Demos, Apps, Tools, AT Firmware.

https://espressif.com/en/support/download/sdks-demos

Products

• ESP32-C3 Series SoCs - Browse through all ESP32-C3 SoCs.

https://espressif.com/en/products/socs?id=ESP32-C3

• ESP32-C3 Series Modules – Browse through all ESP32-C3-based modules.

https://espressif.com/en/products/modules?id=ESP32-C3

• ESP32-C3 Series DevKits - Browse through all ESP32-C3-based devkits.

https://espressif.com/en/products/devkits?id=ESP32-C3

• ESP Product Selector – Find an Espressif hardware product suitable for your needs by comparing or applying filters. https://products.espressif.com/#/product-selector?language=en

Contact Us

• See the tabs Sales Questions, Technical Enquiries, Circuit Schematic & PCB Design Review, Get Samples (Online stores), Become Our Supplier, Comments & Suggestions.

https://espressif.com/en/contact-us/sales-questions

Revision History

Date	Version	Release Notes
2024-01-19	v1.1	 Added Section 3.2 SAR ADC Cannot Sample Sufficient Data in DMA Continuous Conversion Mode after Restart Added chip revision v1.1 Added Chapter 2 Additional Methods Added a note under Table 4
2022-11-14	v1.0	First release



Disclaimer and Copyright Notice

Information in this document, including URL references, is subject to change without notice.

ALL THIRD PARTY'S INFORMATION IN THIS DOCUMENT IS PROVIDED AS IS WITH NO WARRANTIES TO ITS AUTHENTICITY AND ACCURACY.

NO WARRANTY IS PROVIDED TO THIS DOCUMENT FOR ITS MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, NOR DOES ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION OR SAMPLE.

All liability, including liability for infringement of any proprietary rights, relating to use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

The Wi-Fi Alliance Member logo is a trademark of the Wi-Fi Alliance. The Bluetooth logo is a registered trademark of Bluetooth SIG.

All trade names, trademarks and registered trademarks mentioned in this document are property of their respective owners, and are hereby acknowledged.

Copyright © 2024 Espressif Systems (Shanghai) Co., Ltd. All rights reserved.