

**TCB**

**GRANT OF EQUIPMENT  
AUTHORIZATION**

**TCB**

**Certification**

**Issued Under the Authority of the  
Federal Communications Commission**

**By:**

**Timco Engineering, Inc.  
849 NW State Road 45  
Newberry, FL 32669**

**Date of Grant: 03/07/2018**

**Application Dated: 03/07/2018**

**ESPRESSIF SYSTEMS (SHANGHAI) PTE LTD**

**456 Bibo Road Room A201**

**Shanghai, 201203**

**China**

**Attention: Minjie Cai**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER:** 2AC7Z-ESP32SOLO1  
**Name of Grantee:** ESPRESSIF SYSTEMS (SHANGHAI) PTE LTD  
**Equipment Class:** Digital Transmission System  
**Notes:** Wi-Fi & Bluetooth Internet of Things Module  
**Modular Type:** Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	15C	2412.0 - 2462.0	0.515		
	15C	2402.0 - 2480.0	0.007		

Single Modular Approval. Power listed is conducted. Approval is limited to OEM installation only. Compliance of this device in all final host configurations is the responsibility of the Grantee. This device is to be used only for mobile and fixed applications. The end-product must be installed to provide a separation distance of at least 20cm from all persons and must not transmit simultaneously with any other antenna or transmitter or in accordance with FCC multi-transmitter product procedures. OEM integrators must be provided with labeling requirements for finished products. OEM integrators and end-Users must be provided with transmitter operation conditions for satisfying RF exposure compliance. This grant is valid only when the device is sold to OEM integrators and the OEM integrators are instructed to ensure that the end user has no manual instructions to remove or install the device. Separate approval is required for all other operating configurations, including portable configurations with respect to 2.1093 and different antenna configurations. This device has both 20 MHz and 40 MHz bandwidth features.